

## **IN THE CLAIMS**

Please amend the claims as follows:

1. (presently amended) A motorcycle anchoring device for keeping a motorcycle stable and upright while towing comprising, in combination:

a pair of handle covers adapted for positioning over handles of the a motorcycle, the pair of handle covers each having an open inner end and a closed outer end, the open inner end being closable via a drawstring, the drawstring having opposing free ends disposed outwardly from the handle cover, the free ends each having a grommet secured thereto, the pair of handle covers being positioned over the handles of the motorcycle as the motorcycle is positioned atop a transportation trailer; and

a pair of straps having free ends having hooked fasteners, the grommets each receive respective ones of the hooked fasteners from one of the free ends of the straps therein, and one of the hooked fasteners is ~~are~~ then extended downwardly diagonal with the hooked fasteners of the respective other strap free end thereof coupling with the transportation trailer.

2. (presently amended) A motorcycle anchoring device and method for keeping a motorcycle stable and upright while towing comprising, in combination:

providing the a motorcycle;

positioning the motorcycle atop a transportation trailer;

providing pair of handle covers adapted for positioning over handles of the a-motorcycle, the pair of handle covers each having an open inner end and a closed outer end, the open inner end being closable via a drawstring, the drawstring having opposing free ends disposed outwardly of the handle cover, the free ends each having a grommet secured thereto, the pair of handle covers being positioned over the handles of the motorcycle as the motorcycle is positioned atop the transportation trailer, a pair of straps having free ends having hooked fasteners, the grommets each receive respective ones of the hooked fasteners from one of the free ends of the straps therein, and one of the hooked fasteners is ~~are~~ then extended downwardly diagonal with the hooked fasteners of the respective other strap free end thereof coupling with the transportation trailer.